



Configuration options :
3 channel, 4 channel and active

Features RFL4120

Sound quality Class-AB reference amplifier

Full aluminium High-End Construction

Ultra complete active x-over including EBC remote :

- 4, 3 or 2 channel operation
- High pass, low pass or bandpass
- configurations front + sub, front + rear or active filtered

50mm² Power connections

Specifications RFL4120

- Class-AB 4 channel amplifier
- CEA2006 certified output power :
 - 4 x 200 Watts RMS @ 2 ohms and THD+N ≤1%
 - 4 x 120 Watts RMS @ 4 ohms and THD+N ≤1%
 - 2 x 400 Watts RMS bridged @ 4 ohms and THD+N ≤1%
- Active X-over :
 - High pass (HPF) 12dB/oct variable from 40Hz to 5000Hz
 - Low pass (LPF) 24dB/oct variable from 40Hz to 5000Hz
 - Bandpass (BPF) 12dB-24dB/oct variable from 40Hz to 5000Hz
- Signal/noise ratio (1 Watt) : > 98dB
- THD+Noise (Distortion) (1 Watt) : ≤ 0,05%
- Frequency response (±1dB) : 10Hz-90000Hz
- Input sensitivity RCA : 200mV to 6V
- EBC remote (External Bass Control) included
- Dimensions : 525mm x 204mm x 59mm