



Configuration options :
3-4 way active, 3 way active and front-rear-sub

Features

Sound quality Class-AB reference amplifier

Full aluminium High-End Construction

One amp for a complete system!
3 amps including with full x-over

Very efficient and very easy to use

High Quality components

50mm² Power connections

Specifications RFL5300

- Class-AB 5 channel amplifier
- CEA2006 certified output power :
 - 4 ch x 120 Watts RMS @ 2Ω and THD+N ≤1%
 - 4 ch x 80 Watts RMS @ 4Ω and THD+N ≤1%
 - 1 mono ch x 370 Watts RMS @ 2Ω and THD+N ≤1%
 - 1 mono ch x 250 Watts RMS @ 4Ω and THD+N ≤1%
- Active X-over :
 - Channel 1 and 2 : - High pass (HPF) 12dB/oct variable from 40Hz to 5000Hz
 - Channel 3 and 4 : - High pass (HPF) 12dB/oct variable from 40Hz to 800Hz
 - Low pass (LPF) 12dB/oct variable from 40Hz to 5000Hz
 - Bandpass (BPF) is the sum of the LPF and HPF
- Signal/noise ratio (1 Watt) : > 98dB
- THD+Noise (Distortion) (1 Watt) : ≤ 0,05%
- Frequency response (±1dB) : 10Hz-90000Hz
- Input sensitivity : 200mV à 6V
- EBC remote (External Bass Control) included
- Dimensions : 626mm x 204mm x 59mm